



Ecoterra® Hydraulic Oil

Ecoterra Hydraulic Oil is a high-quality, zinc-free antiwear hydraulic oil specifically developed for use in industrial and mobile equipment operating in environmentally sensitive areas. It is specially formulated for reduced environmental impact in case of leaks or spills. It is nontoxic to fish and aquatic species as determined by OECD Test Method 203 1-12, and is classified as inherently biodegradable by the OECD Test Method 301B. It passes the visual “no sheen” requirements of the U.S. EPA Static Sheen Test.

Ecoterra Hydraulic Oil is formulated with an ashless (zinc-free) antiwear additive package to provide excellent wear protection for hydraulic pumps and motors, and to protect hydraulic system components against rust and corrosion. It has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life. It has excellent water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup that can cause poor or sluggish hydraulic system response.

Ecoterra Hydraulic Oil is recommended for use in place of conventional zinc-containing hydraulic oils in applications where there is the possibility of soil or water contamination. It also may be used as a lower-cost alternative to synthetic, readily biodegradable hydraulic fluids. It meets the performance requirements of all major hydraulic pump manufacturers, and is recommended for use in all types of high-pressure, high-speed hydraulic pumps.

Applications

- Hydraulic equipment used in environmentally sensitive areas, such as national parks, wildlife refuges, ski resorts and other recreational areas
- Hydraulic equipment in amusement parks and zoos
- Hydraulic jacks and other equipment in machine shops
- Oil drilling rigs and offshore platforms
- Chain drives
- Electric motor bearings
- Service station lifts
- Hydraulic systems where the equipment manufacturer specifies an ashless, zinc-free antiwear hydraulic oil

**Nontoxic,
Zinc-Free
Antiwear
Hydraulic Oil;
Inherently
Biodegradable**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



Ecoterra Hydraulic Oil meets the requirements of the following industry and OEM specifications:

- Bosch Rexroth RE 90 220
- Denison Hydraulics HF-0, HF-1, HF-2
- DIN 51524 Part 2, Antiwear Hydraulic Oils, Type HLP
- German Steel Industry SEB 181222
- ISO 11158:1997, Family H (Hydraulic Systems), Type HM
- U.S. EPA/U.S. Coast Guard Static Sheen Test, Federal Register Vol. 58, No. 41
- U.S. Steel 127
- Vickers (Eaton) M-2950-S, I-286-S

Features/Benefits

- Nontoxic to aquatic organisms
- Inherently biodegradable
- Does not contain zinc or other heavy metals
- Excellent wear protection for hydraulic pumps and motors
- Excellent oxidation resistance and thermal stability
- Protects against rust and corrosion
- Excellent water-separating properties
- Good foam resistance
- Good low-temperature properties for cold start-ups
- Lower-cost alternative to synthetic biodegradable hydraulic fluids

Note: Ecoterra Hydraulic Oil is **not** compatible with zinc-containing hydraulic oils, and may cause residue, gelling or filter plugging if mixed with such fluids. Mixing the two products will lessen the environmental benefits normally gained by using Ecoterra Hydraulic Oil.



Ecoterra® Hydraulic Oil

Typical Properties

ISO Grade	32	46	68
Specific Gravity @ 60°F	0.862	0.869	0.873
Density, lbs/gal @ 60°F	7.18	7.23	7.27
Color, ASTM D1500	L 0.5	L 1.0	L 1.0
Flash Point (COC), °C (°F)	227 (440)	232 (450)	241 (465)
Pour Point, °C (°F)	-34 (-29)	-33 (-27)	-30 (-22)
Viscosity,			
cSt @ 40°C	32.0	46.0	68.0
cSt @ 100°C	5.4	6.8	8.8
SUS @ 100°F	165	237	352
SUS @ 210°F	44.4	49.0	55.9
Viscosity Index	102	102	102
Acid Number, ASTM D974, mg KOH/g	0.22	0.22	0.22
Copper Corrosion, ASTM D130	1a	1a	1a
Demulsibility, ASTM D1401, minutes to pass	10	15	15
Dielectric Strength, ASTM D877, kv ⁽¹⁾	35	35	35
Foam Test, ASTM D892	Pass	Pass	Pass
Four-Ball Wear, ASTM D4172, Scar Diameter, mm	0.62	0.54	0.44
FZG Scuffing Test, ASTM D5182, Failure Load Stage	>12	>12	>12
Oxidation Stability,			
TOST, ASTM D943-04a, hours	8,000	8,000	8,000
RPVOT, ASTM D2272, minutes	>500	>500	>500
Rust Test, ASTM D665 A&B	Pass	Pass	Pass
Aquatic Toxicity, Rainbow Trout, OECD 203 1-12,			
1000 mg/l, 96 hours, LC ₅₀	Nontoxic	Nontoxic	Nontoxic
Biodegradability in 28 Days, OECD 301B, %	22	22	22

⁽¹⁾At the point of manufacture

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company. Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.