



## **PRODUCT INFORMATION SHEET**

**Product Name: MAXIFLEET 15W40 CG-4 SL**

### **PRODUCT**

Prolube Maxifleet 15W40 is very shear stable, provides excellent protection against wear, corrosion and oxidation and ensures a high degree of engine cleanliness. It is suitable for naturally aspirated and turbo-charged diesel and petrol engines including those running on unleaded petrol.

### **APPLICATION**

Designed for 4 Stroke motors using ULP, PULP, LPG and Diesel fuels where a 15W40 engine oil is specified or indicated. It is specifically designed for pre-1997 North American-style diesel motors requiring low ash engine oils. The primary recommendation is for mixed fleet operations.

### **STANDARDS**

Meets or exceeds the following:

SAE Grade:	15W40	API:	CG-4 SL
Mack:	EO-L	MTU	Type 2
ACEA:	E2/A3/B4	Volvo	VDS
MAN	M3275	Mercedes Benz	228.3/229.1

### **CONTAINER SIZES**

Bulk, 205 Litres, 60 Litres, 20 Litres, 5 Litres.

### **CONTACT**



Pure Fluid Power Pty Ltd  
P.O. Box 1122, Capalaba QLD 4157  
Unit 11, 1440 New Cleveland Road,  
Capalaba West, Qld. 4157.  
Telephone: (07) 3823.5551  
Fax: (07) 3036.6868  
Email: sales@purefluidpower.com.au  
Internet: www.purefluidpower.com.au

Issue Date 26/6/2012