



PRODUCT INFORMATION SHEET

Product Name: PETROLEUM JELLY

PRODUCT

Prolube Pro Petroleum Jelly is a highly refined white petrolatum that meets the purity standards of the latest issues of the United States Pharmacopoeia (USP) and British Pharmacopoeia (BP).

It is a white translucent gel.

Melting Point	50 - 55 °C Typ 53 °C
Congearing Point	48 - 52°C
Viscosity	5.8 - 6.5 cSt @ 100°C Typ 6.2 °C

APPLICATION

Petroleum Jelly is used as a base for cosmetics, as a skin conditioner and in Cosmetics. It can also be used as a softening agent in some printing inks, as a rubber plasticiser and in leather processing.

In industry it can be used as a light duty lubricant, as rust preventive and is an effective water repellent.

It is also used to prevent corrosion on battery terminals.

STANDARDS

Petroleum Jelly is manufactured in compliance with USP 31, BP2008, IP2007 and also conforms to the requirements of US FDA 21CFR 172.880.

CONTAINER SIZES

20 kg 2.5kg.

CONTACT



Pure Fluid Power Pty Ltd
P.O. Box 1122, Capalaba QLD 4157
Unit 11, 1440 New Cleveland Road,
Capalaba West, Qld. 4157.
Telephone: (07) 3823.5551
Fax: (07) 3036.6868
Email: sales@purefluidpower.com.au
Internet: www.purefluidpower.com.au

Issue Date 26/6/2012